





# L92

- Application** Outdoor walkway and area illumination
- IP Rating** 66
- Mounting** Mounts to 24" (610mm), 36" (614mm) or 48" (1219mm) anodized aluminum post. Comes with 24" (610mm) Cabtire lead inside post.
- Electrical** 2.5W, 700mA LED.
- Power Consumption** 3W (at 700mA, 2.5 watt)
- Light Output** 2.5 Watt, 33~86lm
- Warranty** 5 years limited warranty  
Estimated useful life of LED is 50,000 hours.
- Material** Anodized aluminum, insert trim with 1/4" (6mm) thick tempered glass lens. RoHS compliant.
- Weight** 7.15lbs (3.245kg) based on 24" (610mm) post.
- Approval**  

**Type:**

**Project:**

**Modified:**

**Quantity:**

**Notes:**

## Order Guide

L92-2-W22S-S-C-0-A-24-MA

Code	Wattage	Color	Beam	Lens	Angle Bracket	Input Voltage	Post Height(H)	Finish
<b>L92</b>	<b>2</b>	-	-	-	-	-	-	-
	2 = 2.5W	<b>W20S</b> = 2000K, 80+CRI <b>W22S</b> = 2200K, 80+CRI <b>W27S</b> = 2700K, 80+CRI <b>W30S</b> = 3000K, 80+CRI <b>W35S</b> = 3500K, 80+CRI <b>W41S</b> = 4100K, 80+CRI <b>W27H</b> = 2700K, 90+CRI <b>W30H</b> = 3000K, 90+CRI <b>W35H</b> = 3500K, 90+CRI  <i>*W20S AC only</i> <i>*W22S DC only</i>	<b>S</b> = spot (12°) <b>N</b> = narrow flood (30°) <b>W</b> = wide flood (120°)	<b>C</b> = clear <b>F</b> = frosted	<b>0</b> = no angle <b>30</b> = 30° angle <b>X</b> = custom (30° max)	<b>D</b> = DC <i>*DC not available for W20S</i> <b>A</b> = 12V AC <i>*12V AC not available for W22S/W41S &amp; high CRI</i>	<b>24</b> = 24" (610mm) <b>36</b> = 36" (914mm) <b>48</b> = 48" (1219mm)	<b>MA</b> = matte clear anodized

