

Shown as L75C3 canopy mount

Copyright 2011 © MP Lighting



 **MP LIGHTING**<sup>®</sup>  
www.mplighting.com 1 877 708 1184

**L75**  
*4 x 2.5W Spotlight*

# L75

Mounting options

**Application:** Interior directional light for wall, picture, or signage illumination.

**Source:** 4 x 2.5W, 700mA LEDs

**Driver:** Remote 120V primary, 700mA driver (not included).

**LED Input Voltage:** 12V DC

**Power Consumption:** 12W

**Power Supply:** (not included)


**DC** - Recommended TLDAV100W15V. Dimmable with remote dimmable driver and controller, 0~10V dimming. Consult factory.

**Weight:** 0.71lbs (0.321kg).


**Material:** Anodized aluminum. RoHS compliant.

**Mounting:** C1C & C2C mount to custom 2" x 2" octagonal box (included). C1M & C2M retrofit to existing standard octagonal box using custom mounting plate (included). C3 & C4 mount to standard octagonal box (not included). Can also mount to 12V MP Lighting DC, HD, SR and VD rail systems (sold separately).

**Approval:** Dry locations. Approved to US and Canadian standards by CSA.




Shown as C3 canopy mount




C1C




C1M




C2C




C2M



C3




C4




DC



HD




SR



VD

**L75**  
30°  
3000K Std  
343 lm

**Polar Candela Distribution**



Lumen test results provided by LED chip manufacturer

**Illuminance at a Distance**

|      | Center Beam FC | Beam Width |      |
|------|----------------|------------|------|
| 4.0' | 76.0           | 2.0'       | 2.1' |
| 5.0' | 48.6           | 2.6'       | 2.6' |
| 6.0' | 33.8           | 3.1'       | 3.1' |
| 7.0' | 24.8           | 3.6'       | 3.6' |
| 8.0' | 19.0           | 4.1'       | 4.1' |
| 9.0' | 15.0           | 4.6'       | 4.6' |

0° Spread: 28.8°    90° Spread: 28.9°

**Note:** Various operating factors may cause differences between lab and field results. As specifications may change without notice, please refer to the LED Lamp Index located in the "Downloads" section of each product webpage for the most current information.

| CODE | MOUNT | COLOR | BEAM | STEM | FINISH |
|------|-------|-------|------|------|--------|
| L75  |       |       |      |      | MA     |

- C1C** = Ø2-3/8" x 1/4" canopy w/ custom octagonal box
- C1M** = Ø2-3/8" x 1/4" canopy w/ retrofit mounting plate
- C2C** = 2-5/8" Sq. x 3/8" canopy w/ custom octagonal box
- C2M** = 2-5/8" Sq. x 3/8" canopy w/ retrofit mounting plate
- C3** = Ø4-5/8" x 1/4" canopy
- C4** = 4-5/8" Sq. x 1/4" canopy
- DC** = dual circuit
- HD** = horizontal double rail
- SR** = single rail
- VD** = vertical double rail

- W27S** = 2700K, std CRI
- W30S** = 3000K, std CRI
- W20H** = 2000K, high CRI
- S** = spot (12°)
- N** = narrow flood (30°)
- F** = flood (60°)

**Note:** Standard CRI has a value of 75~82 while high CRI has 92.

- 1** = 1" (25mm) stem
- X** = custom stem

**MA** = matte clear anodized



t 1.877.708.1184 f 604.708.1185 www.mplighting.com  
16 West 4th Avenue, Vancouver BC V5Y 1G3, Canada