


# L72C1

## Installation Instructions

- 1** Connect fixture wires to low voltage wiring (remote LED driver 700mA constant current).
- 2** Attach mounting plate to electrical box.
- 3** Thread C1 canopy to mounting plate.
- 4** Push in jack connector and thread cap until secure.



**CAUTION**

- Read all instructions.
- **WARNING: RISK OF FIRE OR ELECTRICAL SHOCK:** Do not make or alter any openings in the compartment of wiring or electrical components during installation. Do not alter or add ballasts, or any other electrical components.
- Installation and use of this fixture mounting assembly requires a person familiar with the construction and operation of luminaire electrical systems and the hazards involved, if not qualified, do not attempt installation.
- Turn off power before installation.
- Fixture gets very hot. Do not cover. Keep 9" away from combustible materials.
- 700mA constant current driver only.
- Do not spray water on fixture during cleaning. Avoid using detergents with hand softeners, anti-bacterial agents, glass cleaners or acrylic cleaning products.
- **KEEP THESE INSTALLATION INSTRUCTIONS.**

<b>Parts</b>	<b>Qty.</b>
• LED unit	1
• C1 canopy	1
• Cross pan head screws	2
• Mounting plate	1
• Wire connectors	2

**Tools**

- Phillips screwdriver *not included*

**Maintenance**  
Clean using a soft cloth.