


L754

INTERIOR

Wall-mount | For walls, stairs, and ceilings

● Dry location



Ordering Information

Clear Form

Date :	_____	Quantity :	_____
Project :	_____	Note :	_____
Type :	_____		_____

Specifications

Luminaire | Example Code: L754-2-W30H-F-S3

Product	Version	CCT & CRI ¹	Glass Cover	Trim Finish
L754			F	S3
	1 1W 2 2W	W22S 2200K 80+ W27H 2700K 90+ W30H 3000K 90+ W35H 3500K 90+ W41H 4100K 90+	F frosted	Stainless Steel Finish: S3 stainless steel 303

System Components (Ordered Separately)

Remote Driver : _____

* Consult MP Lighting Website or Factory.

Important Notes

Specification

1. Consult MP factory for Colour LED options.
2. Mounting kit is ordered separately. Please consult factory.

Warranty Notes & Disclaimer


Malfunction and damage to product due to incompatible dimming system or misuse will not be covered under warranty. Consult MP Lighting for recommended drivers. If the fixture has an option to be installed with a dimming control system, consult a dimming system manufacturer with minimum load before installing. MP Lighting reserves the right, at its sole discretion, at any time and without notice, to make design changes to any of our products. Consult MP Lighting website for most updated documentation.

L754

INTERIOR

Wall-mount | For walls, stairs, and ceilings

- Dry location



Performance

Wattage	Forward Current	Power Consumption Budget per fixture (including driver)	LED output (Source)	Fixture Output (Delivered)
1W	350mA	1.3W	110 lm	9.1 lm
2W	700mA	2.6W	275 lm	16 lm

Application

Environment	Dry Location approved. IP 52.
Mounting	Recessed mount with coil spring clip. Mounts directly to cabinet millwork, drywall, ceiling tiles ... etc.

Electrical

Power Supplies	Remote LED drivers (120-277V AC input, constant current output): Fixtures to be wired in series.
Control	On/off control Dimming (consult factory): ELV or 0-10V dimming with appropriate drivers Other options (consult factory): TRIAC/MLV, DMX, DALI, Casambi, Power over Ethernet

Luminaire Construction

LED Light Source	W22S = CCT: 2200K, CRI (Ra): 80+, Colour Consistency: 3SDCM W27H = CCT: 2700K, CRI (Ra): 90+, Colour Consistency: 2SDCM W30H = CCT: 3000K, CRI (Ra): 90+, Colour Consistency: 2SDCM W35H = CCT: 3500K, CRI (Ra): 90+, Colour Consistency: 3SDCM (Contact factory for 2SDCM option) W41H = CCT: 4100K, CRI (Ra): 90+, Colour Consistency: 3SDCM
Standard Compliance	✓ADA-compliant ✓WELL standard – Feature 58: Color Quality
Weight	0.1kg (0.22lbs)
Material	Fixture: Stainless steel (303) with polycarbonate lens, RoHS compliant.
Supplied with	Standard installation housing: Coil spring clips X 2 Cable: 2' (610mm) factory-installed wire lead
Warranty & LED Life	5 years limited warranty Estimated useful life of LED is 50,000 hours.

Ordered Separately

System Components	Power Supplies: remote driver Please consult factory or visit Recommended Drivers for available driver options.
-------------------	---

Mounting Options & Dimensions




LED Insert Dimensions

Fixture

Front View

3D View



Beam



Wall Installation | shown with coil spring clips

Fixture



Fixture installed with coil spring clips.



Ceiling Installation | shown with coil spring clips


Fixture

Fixture installed with coil spring clips.



1W, 3000K, 90+ CRI

Polar Candela Distribution




Illuminance at a Distance

Distance		Center Beam fc	Beam Width			
3.0ft	0.91m	0.04fc	9.9ft	3.02m	0.7ft	0.21m
6.0ft	1.83m	0.01fc	19.8ft	6.04m	1.4ft	0.43m
9.0ft	2.74m	0.00fc	29.7ft	9.05m	2.2ft	0.67m
12.0ft	3.66m	0.00fc	39.6ft	12.07m	2.9ft	0.88m
15.0ft	4.57m	0.00fc	49.5ft	15.09m	3.6ft	1.10m
18.0ft	5.49m	0.00fc	59.4ft	18.11m	4.3ft	1.31m

Delivered Lumen: 9.1lm
 ■ Vertical Beam Spread: 117.6°
 ■ Horizontal Beam Spread: 13.7°

2W, 3000K, 90+ CRI

Polar Candela Distribution



Illuminance at a Distance

Distance		Center Beam fc	Beam Width			
3.0ft	0.91m	0.09fc	9.9ft	3.02m	0.7ft	0.21m
6.0ft	1.83m	0.02fc	19.8ft	6.04m	1.4ft	0.43m
9.0ft	2.74m	0.01fc	29.7ft	9.05m	2.2ft	0.67m
12.0ft	3.66m	0.01fc	39.6ft	12.07m	2.9ft	0.88m
15.0ft	4.57m	0.00fc	49.5ft	15.09m	3.6ft	1.10m
18.0ft	5.49m	0.00fc	59.4ft	18.11m	4.3ft	1.31m

Delivered Lumen: 16lm
 ■ Vertical Beam Spread: 117.6°
 ■ Horizontal Beam Spread: 13.7°