



Type:
Project:
Modified:
Quantity:
Notes:

DISCLAIMER - When using a control system, consult dimming system manufacturer with minimum load before installing. Malfunction and damage to product due to improper dimming system installation or misuse will not be covered under warranty. Only DC Drivers are recommended for dimming systems. Consult MP Lighting for recommended drivers.

*MP Lighting reserves the right, at its sole discretion, at any time and without notice, to make design changes to any of our products.

Order Guide

Example: L770-3-W27S-S6

Code	Wattage	Color	Finish
L770	-	-	-
	3 = 3W 6 = 6W <i>*Available 120V. For other voltage options available, please consult factory</i>	3-step MacAdam: W223S 2200K 80+ W273H 2700K 90+ W303H 3000K 90+ W353H 3500K 90+ 2-step MacAdam: W272H 2700K 90+ W302H 3000K 90+ W352H 3500K 90+	S6 = stainless steel 316

L770

Application Exterior/interior wall, stair and walkway.
 Recommended Projects - Commercial, Institutional, Retail, Clinic, Hospitality, Religious, Educational, Architecture.

IP Rating 66

Mounting Mounts to horizontal orientated single gang box, included.

Electrical Integral Non Dimmable Driver 120V - 3W (350mA) and or 120V - 6W (700mA)
 *Consult Factory for Integral Driver 120V / 277V – 6W option with Phase Dimmer and or 0-10V
 *For other inquires please consult factory for remote driver options

Power Consumption 4.0 Watt (at 350 mA, 3.0 Watt)
 8.0 Watt (at 700mA, 6.0 Watt)

Light Output 3.0 Watt , 29 lm
 6.0 Watt, 53 lm
**For photometric data, see page 03*

Warranty 5 years limited warranty
 Estimated useful life of LED is 50,000 hours.

Material Solid anodized aluminum or marine grade stainless steel (316). RoHS compliant.

Weight 1.5lbs (0.68kg).

Approval





PHOTOMETRIC DATA:

3W, 3000K 80+ CRI

Polar Candela Distribution

Illuminance at a Distance

Lumen: 29lm



6W, 3000K 80+ CRI

Polar Candela Distribution

Illuminance at a Distance

Lumen: 53lm

