



Max. load depends on wattage of fixture.
 LED 12 Volt = 12V LED Lighting Fixture

Non-dim: 1 - 35 lights,

Constant Voltage LED Driver

LED10W12VN-01

LED10W12VN-01B with Enclosure

SPEC SHEET

Features:

- 100V-240V full range AC input.

AC Input Voltage:	100 ~ 240V, 50/60Hz
DC Output Voltage:	12V Constant
DC Output Current:	830mA Max
Output Wattage:	10W Max
Power Factor:	0.50 Min
Typical Efficiency:	66%
Short Circuit Protection:	Yes
Overload Protection:	Yes
Dimming Function:	Non-dimmable as a standalone driver. 0-10V Dimmable when used with TLC010i Dimming Controller (ordered separately).
Operating Temperature:	-10° ~ 40°C (14 ~ 104°F)
Maximum Case Temperature:	70°C (158°F)
Humidity (Non-Condensing):	20% ~ 95%
Case Material:	Non Conductive White Plastic
Weight:	66.5g (0.15lb)
Rated:	IP20 for dry location
Approval:	UL



Note: Consult factory for wiring length and details.

***COMES WITH EBX-160-ZP ENCLOSURE**

ORDER CODE	DRIVER ENCLOSURE
LED10W12VN-01	B
Driver	B = driver enclosure (6-1/4" x 5" x 2")

[Project]

[Quantity]

[Notes]



t 604.708.1184 f 604.708.1185 www.mplighting.com
 16 West 4th Avenue, Vancouver BC V5Y 1G3, Canada