

Low Voltage Canopy Mount

X01C4

SPEC SHEET



Material: Machined aluminum with electroplated finish.

Sec. Voltage: 12V (fixture).

Mounting: Rotatable and easy to position. Comes with 60W/120V integral electronic transformer or optional 75W/277V electronic transformer. Mounts to standard J-box (not included).


Shade: Sold separately.

Stem: Available in 1" (25mm) increments. Maximum length 96" (2438mm).

Accessories: Sold separately.

Lamp (not included): MR16, 50W Max. Covered glass recommended. (Note: GE constant color lamp cannot be used with glass shade.) For use with LED type MR16 check lamp manufacture for specification and compatibility.

Approval: Dry locations. Approved to US and Canadian standards by CSA.



Type:

Project:

Modified:

Quantity:

Notes:



cap



metal/glass cone



arc



shroud



louver



filter/spreader

CODE	MOUNT	SHADE*	STEM	ACCESSORIES**	PRI. VOLTAGE	FINISH
X01	C4					

NS = no shade
SC = solid metal cap
SCB = solid metal cap, black
PC = perforated metal cap
PCB = perforated metal cap, black
SM = solid metal cone
SMB = solid metal cone, black
PM = perforated metal cone
PMB = perforated metal cone, black
FR = frosted glass cone
AM = amber glass cone
BL = blue glass cone
MA = mesh arc

1 = 1" (25mm)
X = custom length

NA = no accessory
SH = metal shroud
SHB = metal shroud, black
ELB = eggcrate louver, black
BE = beam elongator
CS = crystal spreader
IR = infrared filter
MS = mistlite spreader
UV = ultraviolet filter
LSB = long shroud, black
LH = accessory holder***

1 = 120V
2 = 277V
4 = 230V~240V

MC = matte chrome
BN = brushed nickel

**Can select multiple items. Please specify.
 ***Accessory holder required with accessories.

[✓] MPLIGHTING®

t 1.877.708.1184 f 604.708.1185 www.mplighting.com
16 West 4th Avenue, Vancouver BC V5Y 1G3, Canada

***Note:** Shades are not recommended with LED lamps.