

X01SR

Material Machined aluminum with electroplated finish

Sec. Voltage 12V (fixture)

Mounting Rotatable and easy to position. Designed for use on MP single

rail (SR) system (sold separately).

Stem Available in 1"(25mm) increments. Max. 96"(2438mm).

Shade Sold separately.

Accessories Sold separately.

Warranty 5 years limited warranty

Estimated useful life of LED is 50,000 hours.

Lamp (not MR16, 50W Max. Covered glass recommended. (Note: included)

GE constant color lamp cannot be used with glass shade.)


For use with LED type MR16 check lamp manufacture for

specification and compatibility.

Approval Dry locations. Approved to US and Canadian standards by



Dimension



Type: Project:

Modified:

Quantity:

Notes:

DISCLAIMER - When using a control system, consult dimming system manufacturer with minimum load before installing. Malfunction and damage to product due to improper dimming system installation or misuse will not be covered under warranty. Only DC Drivers are recommended for dimming systems. Consult MP Lighting for recommended drivers.

*MP Lighting reserves the right, at its sole discretion, at any time and without notice, to make design changes to any of our products.

Order Guide

Example: X01-SR-NS-0-NA-MC

Code	Mounting		Shade (optional)	Stem	Accessories (optional)	Finish
X01	SR	_ •				•
	SR = single rail		NS = no shade SM = solid metal cone SMB = solid metal cone, black *not recommneded with LED lamp	1 = 1"(25mm) X = custom	NA = no accessory SH = metal shroud SHB = metal shroud, black ELB = eggcrate louver, black BE = beam elongator CS = crystal spreader IR = infrared filter MS = mistlite spreader UV = ultraviolet filter LSB = long shroud, black LH = accessory holder***	MC = matte chrome BN = brushed nickel
					*Can select multiple items. Please specify. *Accessory holder required with accessories.	



www.mplighting.com t 1.877.708.1184 f 604.708.1185