



X06C

- Material** Machined aluminum with electroplated finish
- Sec. Voltage** 12V (fixture)
- Mounting**
 - C1** - Rotatable and easy to position. Canopy retrofit to octagonal backbox using custom mounting plate (included). Requires remote class II transformer (not included).
 - C3** - Rotatable and easy to position. Powers with remote 277V magnetic transformer (not included). Mounts to octagonal backbox (not included).
 - C4** - Rotatable and easy to position. Powers with remote 277V magnetic transformer (not included). Mounts to octagonal backbox (not included).
 - C21** - Rotatable and easy to position. Mounts to octagonal backbox using spring clips
- Stem** Available in 1" (25mm) increments. Max. 96" (2438mm)
- Shade** Sold separately.
- Accessories** Sold separately.
- Warranty** 5 years limited warranty
Estimated useful life of LED is 50,000 hours.
- Lamp (not included)** MR16, 50W Max. Covered glass recommended. (GE constant color lamp cannot be used with glass shade.) Also compatible with LED MR16 lamps, SORRA LED MR 16 lamps (10W max.) are recommended (SORAA lamp cannot be used with shade).

Approval Dry locations. Approved to US and Canadian standards by CSA.



- Type:**
- Project:**
- Modified:**
- Quantity:**
- Notes:**

DISCLAIMER - When using a control system, consult dimming system manufacturer with minimum load before installing. Malfunction and damage to product due to improper dimming system installation or misuse will not be covered under warranty. Only DC Drivers are recommended for dimming systems. Consult MP Lighting for recommended drivers.

*MP Lighting reserves the right, at its sole discretion, at any time and without notice, to make design changes to any of our products.

Order Guide

Example: X06-C1-NS-1-NA-MC

Code	Mounting	Shade (optional)	Stem	Accessories (optional)	Finish
X06					
	C1 = 2-3/8" (60mm) x 1/4" (6.35mm) C3 = 4-5/8" (117mm) x 1/4" (6.35mm) C4 = 4-5/8" (117mm) x 1/4" (6.35mm) C21 = 2" (50.8mm) x 1/16" (1.59mm) with spring mount	NS = no shade SM = solid metal cone SMB = solid metal cone, black	1 = 1" (25mm) X = custom	NA = no accessory SH = metal shroud SHB = metal shroud, black ELB = eggcrate louver, black BE = beam elongator CS = crystal spreader IR = infrared filter MS = mistlite spreader UV = ultraviolet filter LSB = long shroud, black LH = accessory holder***	MC = matte chrome BN = brushed nickel BA = black anodized


*Can select multiple items. Please specify.
 ***Accessory holder required with accessories.

CANOPY OPTIONS & DIMENSION DRAWINGS


Canopy Images



C1
2-3/8" (60mm) x 1/4" (6.35mm)



C3
4-5/8" (117mm) x 1/4" (6.35mm)



C4
4-5/8" (117mm) x 1/4" (6.35mm)



C21
2" (50.8mm) x 1/16" (1.59mm)
with spring mount

