




X42 C6

- Material** Machined aluminum with electroplated finish.
- Sec. Voltage** 12V (fixture)
- Mounting** C6 canopy 5-7/8 Sq. x 1-1/2 (150mm Sq. x 38mm) mounts to ceiling with buried electrical box. 120V/150W electronic auto-reset transformer included.
- Shade** No shade available.
- Stem** Standard 2" (51mm). Custom stem available in 1" (25mm) increments. Maximum length 96" (2438mm).
- Accessories** Sold separately.
- Lamp (not included)** MR16, 50W Max. Covered glass recommended. (Note: GE constant color lamp cannot be used with glass shade.) Also SORAA LED MR 16 lamps (10W max.) are recommended. For use with LED type MR16 check lamp manufacture for specification and compatibility.
- Warranty** - 5 years limited warranty
- Estimated useful life of LED is 50,000 hours.
- Approval** Dry locations. Approved to US and Canadian standards by CSA.



Accessories:



Type:

Project:

Modified:

Quantity:

Notes:

Code	Mount	Shade	Stem*	Accessories	Pri.voltage	Finish
X42	C6	-			1	-
C6	5-7/8" Sq. x 1-1/2" canopy	NS no shade SC solid metal cap SCB solid metal cap, black	2 2" (51mm) X custom length <small>*Custom length available in 1" increments.</small>	NA no accessory SH metal shroud SHB metal shroud, black ELB eggcrate louver, black BE beam elongator CS crystal spreader IR infrared filter MS mistlite spreader UV ultraviolet filter LH accessory holder	1 120V	MC matte chrome

- Multiple accessories can be selected.
- Accessory holder required with accessories