



X51SR

Material: Machined aluminum with electroplated finish.

Sec. Voltage: 12V (fixture).

Mounting: Rotatable and easy to position. Designed for use on MP single rail (SR) system (sold separately).

Shade: Solid metal cap included.

Stem: Standard 2" (51mm). Custom stem available in 1" (25mm) increments. Maximum length 96" (2438mm).

Accessories: Metal shroud included. Other accessories sold separately.

Lamp (Not included): MR16, 50W Max. Covered glass recommended. Also compatible with LED MR16 lamps. SORRA lamps (10W max.) are recommended (Note: SORAA lamp cannot be used with shade).

Approval: Dry locations. Approved to US and Canadian standards by CSA.



Shades / Accessories:



Type:


Project:

Modified:

Quantity:

Notes:

Dimension:



Code	Mount	Shade*	Stem	Accessories**	Finish
X51	SR	-		-	

SR = single rail

NC = no cap
 SC = solid metal cap
 SCB = solid metal cap, black

2 = 2" (51mm)
 X = custom length (Custom length available in 1" increments. Maximum length for ceiling is 96" and 16" for SF mount.)

NA = no accessory
 SH = metal shroud
 SHB = metal shroud, black
 ELB = eggcrate louver, black
 BE = beam elongator
 CS = crystal spreader
 IR = infrared filter
 MS = mistite spreader
 UV = ultraviolet filter

MC = matte chrome
 BN = brushed nickel

**Multiple accessories can be selected.