L397

INTERIOR

Wall-mount | For walls, and stairs

- Dry location

Ordering Information

Clear Form

Date : _____

Project : _____

Type : _____

Quantity : _____

Note : _____

Specifications

Luminaire | Example Code: L397-2-W30H-F-6

Product	Version	CCT & CRI [1]	Lens	Trim Finish
L397			**F**	**S6**
	1 1W **2** 2W	**W22S** 2200K 80+ **W27H** 2700K 90+ **W30H** 3000K 90+ **W35H** 3500K 90+ **W40H** 4000K 90+	**F** frosted	**Aluminum Finish:** **MA** matte clear anodized **BK** black powder coated **Stainless Steel Finish:** **S6** stainless steel 316L

System Components (Ordered Separately)

Remote Driver : _____

* Consult MP Lighting Website or Factory.

Important Notes

Specification

1. *Consult MP factory for Colour LED options.*

Warranty Notes & Disclaimer

Malfunction and damage to product due to incompatible dimming system or misuse will not be covered under warranty. Consult MP Lighting for recommended drivers. If the fixture has an option to be installed with a dimming control system, consult a dimming system manufacturer with minimum load before installing. MP Lighting reserves the right, at its sole discretion, at any time and without notice, to make design changes to any of our products. Consult MP Lighting website for most updated documentation.

L397

INTERIOR
Wall-mount | For walls, and stairs

- Dry location

Performance

Wattage	Forward Current	Power Consumption Budget per fixture (including driver)	LED output (Source)	Fixture Output (Delivered)
1W	350mA	1.3W	110 lm	11.4 lm
2W	700mA	2.6W	220 lm	22.6 lm

Application

Environment	Dry Location approved. IP 20.
Mounting	Comes with steel flange that mounts to pre-installed standard 4" (102mm) octagonal back box (not included).

Electrical

Power Supplies	Remote LED drivers (120-277V AC input, **constant current output**): Fixtures to be wired in series.
Control	**On/off control** **Dimming (consult factory):** ELV or 0-10V dimming with appropriate drivers **Other options (consult factory):** TRIAC/MLV, DMX, DALI, Casambi

Luminaire Construction

LED Light Source	**W22S =** CCT: 2200K, CRI (Ra): 80+, Colour Consistency: 3SDCM **W27H =** CCT: 2700K, CRI (Ra): 90+, Colour Consistency: 2SDCM **W30H =** CCT: 3000K, CRI (Ra): 90+, Colour Consistency: 2SDCM **W35H =** CCT: 3500K, CRI (Ra): 90+, Colour Consistency: 2SDCM **W40H =** CCT: 4000K, CRI (Ra): 90+, Colour Consistency: 2SDCM
Weight	N/A
Material	Stainless steel (316L) with ploycarbonate lens, RoHS compliant.
Supplied with	Comes with a steel mounting flange.
Warranty & LED Life	5 years limited warranty Estimated useful life of LED is 50,000 hours.

Ordered Separately

System Components	**Power supplies:** remote driver

Mounting Options & Dimensions

LED Insert Dimensions

Fixture



Front View



3D View

Beam



Ceiling, Wall, and Stair Riser Installation (shown with a mounting flange)

Wall installation



Appendix

Aluminum Finishes



MA matte clear anodized

BK black powder coated

S6 stainless steel (316L)

1W, 3000K, 90+ CRI

Polar Candela Distribution



Illuminance at a Distance

Distance		Center Beam fc	Beam Width			
1.5ft	0.46m	0.72fc	10.2ft	3.1m	21.6ft	6.6m
3.0ft	0.91m	0.18fc	20.4ft	6.2m	43.1ft	13.1m
4.5ft	1.37m	0.08fc	30.7ft	9.3m	64.7ft	19.7m
6.0ft	1.83m	0.04fc	40.9ft	12.4m	86.3ft	26.3m
7.5ft	2.29m	0.03fc	51.1ft	15.6m	107.9ft	32.9m
9.0ft	2.74m	0.02fc	61.3ft	18.7m	129.4ft	39.4m

Delivered Lumen: 11.4lm
Vertical Beam Spread: 147.3°
Horizontal Beam Spread: 164.2°

2W, 3000K, 90+ CRI

Polar Candela Distribution



Illuminance at a Distance

Distance		Center Beam fc	Beam Width			
1.5ft	0.46m	1.43fc	9.6ft	2.9m	21.2ft	6.4m
3.0ft	0.91m	0.36fc	19.1ft	5.8m	42.4ft	517.2m
4.5ft	1.37m	0.16fc	28.7ft	8.7m	63.6ft	776.4m
6.0ft	1.83m	0.09fc	38.3ft	11.6m	84.7ft	1035m
7.5ft	2.29m	0.06fc	47.9ft	14.6m	105.9ft	1295m
9.0ft	2.74m	0.04fc	57.4ft	17.5m	127.1ft	1553m

Delivered Lumen: 22.6lm
Vertical Beam Spread: 145.2°
Horizontal Beam Spread: 163.9°