LED4W700iP-01

CONSTANT CURRENT

4W, 700mA, ELV dimmable, 120V AC Input

O Damp and Dry location





Ordering Information					Clear Form
Date:				Quantity:	
Project:				Note:	
Type:					
Specification	ns				
LED Driver Exa	ample Code: LED4\	N700iP-01-B			
Product	Enclosure				
LED4W700iP-01	В	_			
	B driver enclosure				

Important Notes

Warranty Notes & Disclaimer


 $MP\ Lighting\ reserves\ the\ right, at\ its\ sole\ discretion,\ at\ any\ time\ and\ without\ notice,\ to\ make\ improvements\ and\ innovations\ to\ any\ of\ our\ products.\ Consult\ MP\ Lighting\ website\ for\ further\ details.$

- Do not install on-off switch at the output (load) side of a constant current LED driver as it will damage the fixture(s) and will void the warranty on both driver and fixture(s).
 Fixtures must be wired as per MP Lighting's instruction (series wiring for constant current driver and
- Fixtures must be wired as per MP Lighting's instruction (series wiring for constant current driver and parallel wiring for constant voltage drivers.) Failures due to improper installation will void warranty.

Dimensions

Driver

2-1/2' 63mm Driver with Enclosure (EBX-160-ZP)



LED4W700iP-01

CONSTANT CURRENT

4W, 700mA, ELV dimmable, 120V AC Input

O Damp and Dry location





Performance

Input Output Efficiency

Voltage: 120V AC, 50/60 Hz Voltage: 2.5~6V DC Power Factor: 0.9 minimum.

Current: 700mA Constant **Typical Efficiency:** 80%

Wattage: 4W maximum

Controls

Dimming Protocols ELV dimmable. Can be used in both dimming & non-dimming systems.

Dimming Range 10%~100%

Recommended Load

Driver Load Typically used for 2W LED fixtures with the load below:

Systems		Load	Load		
Input Voltage	System Dimming Option	Minimum	Maximum		
120V only	Dimming	1	1		
	Non- Dimming	1	1		
> 120V~277V	Dimming	1	1		
	Non- Dimming	1	1		

Application

Environments Damp and Dry Location approved.

Ambient Temperature -30°C (-22°F) minimum.

Case Temperature 80°C (176°F) maximum.

Driver Protection Short Circuit, Overload & Over-voltage protection.

Weight 150g (0.33lb).

Case Material Metal

Wiring Diagram

Dimming | For use with 1 x 2W LED lighting fixtures (700mA), wired in series



O 700mA LED Lighting Fixture

Non-Dimming | For use with 1 x 2W LED lighting fixtures (700mA), wired in series



O 700mA LED Lighting Fixture