



Image shows no shade (NS) and no accessory (NA).

Low Voltage Single Rail Black

X06SRB

SPEC SHEET

Material: Machined aluminum with electroplated finish.

Sec. Voltage: 12V (fixture).

Mounting: Rotatable and easy to position. Designed for use on MP single rail (SR) system (sold separately).

Fixture Height: Overall standard 7" height. Stem length can be shorten upon request.

Lamp (not included): MR16, 50W Max. Covered glass recommended. (Note: GE constant color lamp cannot be used with glass shade.) For use with LED type MR16 check lamp manufacture for specification and compatibility.

Approval: Dry locations. Approved to US and Canadian standards by CSA.




Type:
Project:

Modified:

Quantity:

Notes:



CODE	MOUNT	SHADE*	ACCESSORIES**
X06	SRB	-	

SRB = single rail black

NS = no shade
SCB = solid metal cap, black
SMB = solid metal cone, black

***Note:** Shades are not recommended with LED lamps.

NA = no accessory
SH = metal shroud
SHB = metal shroud, black
ELB = eggcrate louver, black
BE = beam elongator
CS = crystal spreader
IR = infrared filter
MS = mistlite spreader
UV = ultraviolet filter
LSB = long shroud, black
LH = accessory holder***

**Can select multiple items. Please specify.

***Accessory holder required with accessories.

[M] MP LIGHTING®

t 1.877.708.1184 f 604.708.1185 www.mplighting.com
16 West 4th Avenue, Vancouver BC V5Y 1G3, Canada