[∽] MPLIGHTING

INTERIOR Spotlight | For ceilings, walls & counters

Dry location





Ordering Information	Clear Form
Date :	Quantity :
Project :	Note :
Туре :	

Specifications

Luminaire | Example Code: X31-CS-17-MC

Product	Mounting	Antenna	Finish ¹
X31	cs		МС
	CS cable system	17 9-3/4" to 16-1/2" (248mm to 419mm)	MC matte chrome

System Components (Ordered Separately)

Remote Driver :

* Consult MP Lighting Website or Factory.

Important Notes

Specification

 Refer to Appendix or MP Lighting website for complete look of luminaire with different finish options.

Warranty Notes & Disclaimer

Malfunction and damage to product due to incompatible dimming system or misuse will not be covered under warranty. Consult MP Lighting for recommended drivers. If the fixture has an option to be installed with a dimming control system, consult a dimming system manufacturer with minimum load before installing. MP Lighting reserves the right, at its sole discretion, at any time and without notice, to make design changes to any of our products. Consult MP Lighting website for most updated documentation.


[∽] MPLIGHTING

X31CS INTERIOR Spotlight For ceilings, wal • Dry location $ceess c \in C$	Is & counters	
Application		
Environment	Dry Location approved. IP 20.	
Mounting	CS: Rotatable and easy to position. Designed for use on MP cable system (CS) (sold separately).	
Luminaire Construction		
LED Light Source	Lamp supplied by others. Recommended: MR16, 50 W max or LED MR16 (SORAA lamp) 10W max.	
Weight	N/A	
Material	Fixture: Machined aluminum with electroplated finish.	
Supplied with	Standard installation housing: Comes with an adapter plate, two #8-32 screws, and wire nuts.	
Warranty & LED Life	5 years limited warranty. Estimated useful life of LED is 50,000 hours.	
Ordered Separately		

Ordered Separately	
System Components	Lamp.

Mounting Options & Dimensions

LED Fixture Dimensions





Beam (with lamp supplied by others)

CS









Appendix



MC matte chrome