

X45CD C8

Material	Machined aluminum with electroplated finish
Sec. Voltage	12V (fixture)
Mounting	CD-C8 - C8 canopy 6-1/2" x 6" x 1-7/8" (165mm x 153mm x 48mm) mounts to ceiling with buried electrical box. 120V/150W electronic autoreset transformer included.
Stem	Default 2"(51mm) Available in 1"(25mm) increments. Max. 96"(2438mm)
Accessories	Sold separately.
Warranty	5 years limited warranty Estimated useful life of LED is 50,000 hours.
Lamp (not included)	MR16, 50W Max. Covered glass recommended. (Note: GE constant color lamp cannot be used with glass shade.) For use with LED type MR16 check lamp manufacture for specification and compatibility.
Approval	Dry locations. Approved to US and Canadian standards by CSA. $c \in \mathbb{G}^{\mathbb{R}}_{US}$
Dimesion	6-1/2"(165mm) 1-7/8" 197/mm 03-1/8"(080mm) 03-1/8"(080mm) 6"(153mm) 1-7/8" 03-1/8" 0(79mm)

Type:

Project:

Modified:

Quantity:

Notes:

DISCLAIMER - When using a control system, consult dimming system manufacturer with minimum load before installing. Malfunction and damage to product due to improper dimming system installation or misuse will not be covered under warranty. Only DC Drivers are recommended for dimming systems. Consult MP Lighting for recommended drivers.

*MP Lighting reserves the right, at its sole discretion, at any time and without notice, to make design changes to any of our products.

Order Guide

Example:)	X45-CD-2-NA-1-6-MC					
Code	Mounting	Stem	Accessories (optional)	Primary Voltage	Canopy	Finish
X45	CD	- 2	NA	1	8	•
		2 = 2" <i>(51mm)</i> X = custom	$\mathbf{NA} = \mathbf{no} \ \mathbf{accessory}$	1 = 120V	8 = C8	MC = matte chrome
		*Custom length available in 1" (25mm) incre- ments up to 96" (2438mm) long				